

Panafill

FWP

LOW DENSITY FIBREBOARD



This funky room with Panafill wall panels is just one of the many uses of Panafill low-density fibreboard. Lightweight, natural wood fibre based Panafill is easy to paint, polypurethane, cut, shape or laminate offering a host of indoor applications, styles and flair.

Panafill



Tatami Mats (Kermadec Restaurant)



Tatami Mat Construction



Office Partitioning



Panafill Panel

Panafill applications include

- Fixed and demountable partitions
- Base board in soft and hard finishings
- Interior core lining for Tatami mats.

Painted Panafill sheets provide a textured surface and look great when framed or jointed together with contrasting painted or natural timber battens.

Easily covered with fabrics - create your own design style to enhance your decor.

Nominal size 2400 x 1200mm with the following sheet thicknesses

- 8mm
- 12mm
- 15mm
- 18mm
- 20mm

The Quiet Performer

Panafill is widely known and used as a behind-the-scenes-performer - its uses range from core material for doors, to thermal and sound insulation, to fabric covered fashion acoustic partitions.

Lightweight and easily handled, Panafill is ideal for a wide range of interior applications. Where a low density panel is needed to add a fashion element to new or existing decor, or to provide sound absorption, choose Panafill.

For Technical Information Freephone
Fletcher Wood Panels Limited Customer Services on

0800 800 080

FWP

Fletcher Wood Panels Limited

25 O'Rourke Road, Penrose, Auckland PO Box 12-135, Auckland 1135, New Zealand
Ph 04-9-529 9780, Fax 04-9-579 1125 Marketing and International Fax 04-9-579 0995
Customer Services Ph 800 800 080

